



Product Variant

Twin 5

Art. no. 9344526xx

Available Products with Grid Connection Boxes *

Grid Connection Fuses

3 x 25 A

Art. no.

934452650

Compliant with

Connection requirements for 3x 25 A charging stations V2.1

Short-circuit protection in GCB (Grid connection box)

3 x Fuse 25 A gG

Short-circuit protection on board

3 x Fuse 20 A gG

Short-circuit protection setup selectivity

✓

* From Jul 1st, 2023 the GCB will not be supplied anymore in the Netherlands in accordance with the "Connection requirements V3.0". The GCB will be changed to CAM (Compact connection module, "Compacte Aansluit Module" in Dutch).

General Product Specifications

Number of sockets

2

Types of sockets

2 x Type 2 socket, in accordance with IEC62196-2

Authentication methods

Plug & Charge
RFID charge card
ISO15118 Auto charge and Plug & Charge
Central system
Third-party apps

Status indication

User interface equipped with LEDs

Energy meter, per socket

MID certified 4 quadrant meter

Supported power systems

TN-S, TN-C-S, TT, IT *
3 x 400 V +N
3 x 230 V w/o N

Nominal output voltage (+/- 10%)

400 V (3 x 230 V)

Maximum design current

64 A per phase

Maximum design power

1-phase: 7.4 kW
3-phase: 22 kW

Main Switch

4P, 80 A, 400 V
Cable clamps on main switch, range:
• 16 mm² per wire: solid wire (PVC cable)
• Max. 6 mm² per wire: stranded wire with ferrules (PVC cable)



Cable diameters	<p>Tulles available for:</p> <ul style="list-style-type: none"> • 1 x 14-54 mm: Mains power in • 2 x 13-34 mm: Power out for (max.) 2 Twin 5 in Smart Charging Network • 3 x 12-18 mm: Ethernet cable <p>Cable clamp, range for 2-7 mm: cable for grounding electrode</p>
Contactors	<p>Per phase controllable relays Integrated per socket, simultaneous activation of all phases Extra safety relay in series for emergency situations</p>
Overcurrent protection	<p>Integrated in firmware, overcurrent response scenarios: >110% after 100 seconds >125% after 5 seconds</p>
Short-circuit protection	<p>MCB or fuse up to 40 A per phase * *</p>
Residual current protection	<p>Per socket RCD, 30 mA type B Rated breaking capacity: 14 kA Integrated 5 mA DC fault detection, response time 1 to 5 seconds</p>
Available in- and outputs	<p>2 x RJ45 (Ethernet/LAN) RS-485 (Modbus RTU)</p>

* Caution: not all vehicles support the IT system. In that case, or with 3-phase charging, an isolation transformer is required.

* * The presence of a Grid Connection Box (GCB) may reduce the maximum input capacity and limit the output per socket or require Standard Load Balancing.

Smart Charging Network Support *

Maximum number of Twin 5 charging stations with a single grid connection	3
Design optimized for	3 x 35 A
Supported wiring schemes	Star topology Daisy chain
Terminals	5 x 4 connections L1, L2, L3, N, PE
Clamping range	2.5 mm ² – 16 mm ²
Network switch	5 ports, 10/100/1000 Mbps
Recommended cable dimensions * *	3 x 25 A 3 x 35 A
Diameter	5 x 4 mm ² 5 x 6 mm ²
Total length (max.)	80 m 60 m

* Assumes the use of accessory 803995905-ICU.

* * These recommendations are only indicative. The installer is responsible for the correct selection of cables and dimensions appropriate for the installation.



Communication and Protocols

Controller	AHP
Vehicle communication	Mode 3 in accordance with IEC 61851-1 ed. 3 (2017) ISO 15118 communication (optional)
RFID card reader	ISO/IEC 14443A/B, 13.56 MHz MIFARE Classic 1K/4K, MIFARE Ultralight, DESFire (EV1/EV2) Maximum length: 7 bytes
Internet/networking possibilities	GPRS 2G LTE Cat M1 4G Ethernet/LAN
Supported mobile communication bands	2G: EGPRS quad-band: 850 / 900 / 1800 / 1900 MHz 4G: LTE Cat M1 bands: 3, 8, 20
Communication protocol to central system	OCPP 1.6 (JSON) OCPP 1.6 + SE OCPP 2.x (upgradeable)
Supported RJ45 protocols	OCPP TCP/IP
Modbus (master)	TCP/IP

Cyber Security

SIM card	Mini SIM card (2G/4G) APN username and password
Central system authentication	TLS 1.2 x509 2048/4096 bit root certificate
EVSE authentication	HTTP Basic authentication <ul style="list-style-type: none"> with TLS with TLS and Client Side Certificates without TLS
Remote console access (SSH, telnet)	Not supported
Diagnostic files	Encryption: AES 128 bit
Firmware update files	Encryption: AES 256 Signature: ECDSA NIST P384 (SHA384)
EVSE Internal Flash	Smart control board: AES-CBC Switch board: AES 256 bit
Root certificate	Installed in the factory, update through signed UpdateFirmware file, or remote via OCPP management system

Twin 5

Technical Specification



Available Memory

Tokens	Local list: 1000 (Configurable) White list: 1000 (Configurable)
Transaction database	20 000 transactions (Configurable)
Logging for diagnostics	Approx. 45 000 lines

Operating Conditions

Operating temperature	-25°C to +55°C (externally validated)
Relative atmospheric humidity	5 to 95 %
Electrical safety class	Class I
Degree of protection (casing)	IP54
IK protection (mechanical impact)	IK10
Stand-by power consumption	Approx. 20 W

Casing

Type	Charging column
Mounting options	Directly on solid underground or on optional metal or concrete base
Material	Cold-rolled Stainless steel AISI/SAE 304, fine-structure powder coating
Color	RAL 7043 (Traffic Grey B) other colors on request
Locking	Lockable lever with space for 2 Half (Single) Euro cylinders 40/45 mm (not included) Standard key included
Dimensions (H x W x D)	
Casing	1385 x 335 x 220 mm
Packaging	1490 x 390 x 300 mm
Internal space for Grid Connection Box	634 x 220 x 160 mm
Weight	
Casing	Approx. 40 kg
Total, incl. packaging	Approx. 42.5 kg

Twin 5

Technical Specification



External protection according to EV/ZE-Ready

IEC 61000-4-16 or IEC 61543

Frequency range	Level 3		Level 4	
	Continuous test V_{rms} (V)	Current (mA)	Continuous test V_{rms} (V)	Current (mA)
1 kHz - 1.5 kHz	1	6.6	3	20
1.5 kHz - 15 kHz	1-10	6.6-66	3-30	20-200
15 kHz - 150 kHz	10	66	30	200

Standard and Selectable Settings Ex-Works

Description	Options
Authorization	Plug & Charge RFID * Autocharge *
Maximum charging current	16 A 32 A *
Smart Charging	Off Standard Load Balancing * Active Load Balancing (Modbus TCP/IP and Modbus RTU) *
User availability if temporarily off-line	Accept all RFID passes Only accept locally registered RFID cards Charging not possible
Response if when plug is released on vehicle side	Stop transactions and release the plug Pause charging until cable plugged back in
Selected backend	Stand alone; ICU Connect * Others options *
Mobile network communication options *	2G: GPRS 4G: LTE-M Ethernet UTP/LAN Autodetect

The settings marked with a * may result in additional costs when purchasing your charging station. The default settings are always mentioned first. For more information about the options, please contact your sales representative.

Twin 5

Technical Specification



Accessories

Product variant	Article no.
<i>General accessories for Twin 5</i>	
Concrete base	833829300-ICU
Dimensions (H x W x D)	570 x 350 x 220 mm
Weight	42 kg
Metal base	803828601-ICU
Dimensions (H x W x D)	598 x 204 x 300 mm
Weight	7.8 kg
Packaging (H x W x D)	50 x 295 x 620 mm
Additional RFID Card	203120010-ICU
Smart Charging Network (SCN) extension module Twin 5	803995905-ICU
Dimensions (H x W x D)	100 x 150 x 100 mm
Weight	Approx. 1.5 kg